

Product Chart

Reinforcing Steel













Product Chart

For Reinforcing Steel | AS/NZS 4671

DON'T TAKE A RISK - specify and insist on using Pacific Steel™ product in your next project.

AS/NZS Codes	Market Grade	Grade Description	Bar Diameters Available (mm)	Length Range	Specify
D300E	D 4-Rib	G300E Deformed Bar	12, 16	6m - 12m	PACIFIC™ 300E deformed bar
	Bar Markings]3]0]0][5]]])]	
D300E	D 2-Rib	G300E Deformed Bar	20*, 25*, 32* On application only	6m - 18m	PACIFIC™ 300E deformed bar
	Bar Markings		PACIFIF]3]o]o]E]]]]]	
R500E	HR	G500E Plain Bar	12, 16, 20	6m - 18m	PACIFIC™ 500E micro alloyed plain bar/coil/ductile rod
		G500E Plain Coil (Rod for Mesh)	5.5, 6.1, 7.0, 7.5, 8.0, 9.0	Ductile Rod	
		G500E Plain Coil (Reo)	10, 12, 16	Reinforcing Coil	
	Bar Markings			0	
D500E	H 4-Rib	G500E Deformed Bar	12, 16,	6m - 18m	PACIFIC™ 500E micro alloyed deformed bar/coil
		G500E Deformed Coil	10, 12, 16	Reinforcing Coil	
	Bar Markings			5 0 0 E	
D500E	H 2-Rib	G500E Deformed Bar	20, 25, 32, 40, 50	6m - 18m	PACIFIC™ 500E micro alloyed deformed bar
	Bar Markings				
D500E	RB	Reid Threaded Bar	12, 16, 20, 25, 32	6m - 18m	PACIFIC™ 500E micro alloyed REIDBAR™
	Bar Markings				

^{*}On application only - minimum quantity of 100tn per length applies

Bar Lengths:

- » Bars are available in standard 1m increments between the indicated ranges e.g. 7m, 8m etc.
- » On inquiry, lengths less than 1m increments may be produced e.g. 9.2m, 12.5m, etc (further T&C's apply)
- » Non-standard lengths are 'on application only'

Coil Products:

» All coils are approximately 1.45 tonnes

Bar Lengths by Location:

- » Auckland standard lengths are 6m 18m.
- » Other locations standard lengths are 6m 15m.
 Bars 16m to 21m may be arranged (further T&C's apply

All products are subject to mill confirmation & Pacific Steel terms of sale apply (visit pacificsteel.co.nz)

In line with our reinforcing brand update to PACIFIC STEEL™, the historical 'SEISMIC" bar marking updated to 'PACIFIC'™ from June 2024. SEISMIC" continues to be a registered trademark of Pacific Steel (NZ) Ltd, and 300E/500E products featuring the former bar marking may still be observed in the market during this transition and treated as compliant.







